



Part Number: D3C1720N



Electrical Specifications

Frequency Range (GHz):	1.7 – 2.0
Isolation (dB):	20 MIN
Insertion Loss (dB):	0.4 MAX
VSWR:	1.25:1 MIN
Forward Power (W):	150 AVG 500 PK


Mechanical/Environmental Specifications

Connector Type:	Type-N
Connector Body:	Nickel plated brass
Connector Pin:	Gold plated copper
Load Body:	Brass
Magnetic Shunt:	Nickel plated CRS
Operational Temp:	-20°C to +65°C
Weight (oz)	3.0 MAX

D3C1720N Dimensions



D3C1720N-3 Dimensions



Dimensions are in inches
Tolerance
XX ±0.03
XXX ±0.010

Type of Device	PN Suffix	Connector Configuration Input / Output	PN Example
Single Junction Circulator 3-Port Device Port 1 / Port 2 / Port 3	No Dash	Female / Female / Female	D3C1720N
	-1	Male / Female / Female	D3C1720N-1
	-2	Female / Male / Female	D3C1720N-2
	-3	Male / Male / Male	D3C1720N-3
	-4	Female / Female / Male	D3C1720N-4
	-5	Male / Female / Male	D3C1720N-5
	-6	Male / Male / Female	D3C1720N-6
	-7	Female / Male / Male	D3C1720N-7



MEASURED DATA

Part Number: D3C1720N, P1→P2, P3 Terminated with 50Ω, +25°C

