



Part Number: D3C1023Y-77K



Electrical Specifications

Frequency Range (GHz):	10.3 – 23.0
Isolation (dB):	20 MIN
Insertion Loss (dB):	1.0 MAX
Return Loss (dB):	14 MIN
Forward Power (W):	10 AVG
	30 PK


Mechanical/Environmental Specifications

Connector Type:	SMA
Connector Body:	Passivated stainless steel
Connector Pin:	Gold plated copper
Magnetic Shunt:	Nickel plated CRS
Optimized Temperature:	< 77K
Weight (oz)	0.9 MAX

D3C1023Y-77K



D3C1023Y-77K-3



Dimensions are in inches
Tolerance
XX ±0.03
XXX ±0.010

Type of Device	PN Suffix	Connector Configuration Port 1 / Port 2 / Port 3	PN Example
Single Junction Circulator 3-Port Device Port 1 / Port 2 / Port 3	No Dash	Female / Female / Female	D3C1023Y-77K
	-1	Male / Female / Female	D3C1023Y-77K-1
	-2	Female / Male / Female	D3C1023Y-77K-2
	-3	Male / Male / Male	D3C1023Y-77K-3
	-4	Female / Female / Male	D3C1023Y-77K-4
	-5	Male / Female / Male	D3C1023Y-77K-5
	-6	Male / Male / Female	D3C1023Y-77K-6
	-7	Female / Male / Male	D3C1023Y-77K-7



MEASURED DATA

Part Number: D3C1023Y-77K, P1→P2, P3 Terminated with 50Ω, Measured at 77K

